

4/8 Willington Street, Archerfield, Queensland, Australia 4108

High Torque battery tool

Product Specs



- Torque Range**
 - 4 models: 1300/2400/3400/4000 Nm
- Dual trigger**
 - Both triggers need to be pressed
 - Minimize risk of injury
- Accessory Bus**
 - Possibility to mount Barcode scanner
- Multi functional LED**
 - White spotlight for dark areas
 - OK/NOK feedback for operator
- Battery**
 - 36 V smart battery
- Ergonomics**
 - Well balanced
 - D Handle for robustness & safety
- Operator control & feedback**
 - Display with 3 buttons
 - Pset Selection / Quick Torq.
 - Simple interface for operator
- Drive & performance**
 - Backup battery
 - High performance motor
 - Transducer with 5% accuracy

Atlas Copco

Model	Square drive	Torque range Nm	Speed rpm	Weight kg*	Length mm	CS distance mm*
ETP SRB81-1300 HA	3/4"	390-1300	23	5,5	378	32
ETP SRB81-2400-HA	1"	720-2400	11	6,8	428	35,5
ETP SRB81-3400-HA	1"	1020-3400	5^	8,5	441	55,5
ETP SRB81-4000-HA	1"	1200-4000	3^	8,5	441	55,5

Digital

Set and go

- Ready to use straight out of the box
- Use buttons to set target torque
- OK / NOK, status messages based on torque readings

Smart

Save process data

- Use any device to program tool via WIFI
- Up to 10 psets, up to 10 batches
- Torque, angle or torque + angle target possible
- Possible to work with accessory scanner
- Use any device to download via WIFI
- OK / NOK, status messages based on torque + angle readings

Smart connected

Full functionality with PF6000

- Connect to a PF6000 controller
- Select functionality via type of virtual station
- Use data sent to controller and any other system
- Possibility to add multiple accessories



Contact Titan Technologies for more information